

jp02088782/pn

L2 ANSWER 1 OF 1 JAPIO (C) 2006 JPO on STN
ACCESSION NUMBER: 1990-088782 JAPIO
TITLE: PRODUCTION OF DIAMOND-COATED MEMBER
INVENTOR: SATO YASUSHI; SAITO YUKIO; GOMI KENICHI; NISHIMURA
SHIGEOKI; SAKODA KOTARO
PATENT ASSIGNEE(S): HITACHI LTD
BABCOCK HITACHI KK
PATENT INFORMATION:

PATENT NO	KIND	DATE	ERA	MAIN IPC
JP 02088782	A	19900328	Heisei	C23F017-00

APPLICATION INFORMATION

STN FORMAT: JP 1988-239771 19880927
ORIGINAL: JP63239771 Showa
PRIORITY APPLN. INFO.: JP 1988-239771 19880927
SOURCE: PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined
Applications, Vol. 1990
INT. PATENT CLASSIF.:
MAIN: C23F017-00
SECONDARY: C23F004-00

ABSTRACT:

PURPOSE: To easily produce the title diamond-coated member having excellent adhesion by selectively vapor-etching a binder of Co, etc., on the surface of a cermet substrate, and thereby forming a diamond film on the substrate surface.

CONSTITUTION: The cermet substrate 3 with the surface coated with a binder consisting of Co and/or Ni is set in a reaction vessel 2, the vessel 2 is depressurized by a vacuum pump 5, and a gaseous etchant contg. at least one kind among carbon monoxide, water, and gaseous hydrogen halides is introduced from an inlet pipe 1. The substrate 3 is then heated to a specified temp. by a heater 7, a plasma is produced from a microwave power source 4 through a waveguide 6, and the surface of the substrate 3 is etched. When the etching is finished, a diamond film forming gas is supplied to the reaction vessel 2 from the inlet pipe 1 to produce plasma, and a diamond film is formed on the surface of the substrate 3. By this method, a diamond-coated member having excellent adhesion is easily obtained in a short time.

COPYRIGHT: (C)1990,JPO&Japio